


Axpert Ultra Off-Grid Inverter



- Dual outputs for smart load management • Two independent AC power sources connected and switched automatically
- Built-in current transformer sensor to meet self-consumption application
- Support external BTS (Battery Temperature Sensor) detection • Built-in power status lighting indicators • Built-in 2.8" colored LCD with slide operation • Built-in Wi-Fi for mobile monitoring and OTA firmware upgrade • Supports USB On-the-Go function • Reserved communication port for BMS (RS485, CAN-BUS or RS232) • Support optional GFCI, Rapid shutdown, AFCI detections
- Parallel operation with 6 units

Axpert Ultra Off-Grid Inverter Selection Guide

MODEL	Axpert Ultra 8K	Axpert Ultra 11K
RATED POWER	8000VA/8000W	11000VA/11000W
PARALLEL CAPABILITY	YES, 6 units	
INPUT		
Voltage	230 VAC	
Selectable Voltage Range	170-280 VAC (For Personal Computers) 90-280 VAC (For Home Appliances)	
Frequency Range	50 Hz/60 Hz (Auto sensing)	
OUTPUT		
AC Voltage Regulation (Batt. Mode)	230VAC \pm 5%	
Surge Power	16000VA	22000VA
Efficiency (Peak)	93%	
Transfer Time	10 ms (For Personal Computers) ; 20 ms (For Home Appliances)	
Waveform	Pure sine wave	
BATTERY		
Battery Voltage	48 VDC	
Floating Charge Voltage	54 VDC	
Overcharge Protection	63 VDC	
SOLAR CHARGER & AC CHARGER		
Solar Charger Type	MPPT	
Maximum PV Array Power		
MPPT Range @ Operating Voltage	10000W (5000W x 2)	12000W (6000W x 2)
Maximum PV Array Open Circuit Voltage	90 ~ 450 VDC	
Maximum PV Input Current	500 VDC	
Maximum Solar Charge Current	27A x 2 (MAX 40A)	
Maximum AC Charge Current	150A	150A
Maximum Charge Current	120A	150A
PHYSICAL	150A	150A
Dimension, D x W x H (mm)		
Net Weight (kgs)	145 x 438 x 553.6	
Communication Interface	18.4	
External Current Sensor Port	USB/RS232/RS485/WiFi/Dry-contact/BTS Support optional GFCI, Rapid shutdown, AFCI detection	
OPERATING ENVIRONMENT	Yes, built-in current transformer sensor	
Humidity		
Operating Temperature	5% to 95% Relative Humidity(Non-condensing)	
Storage Temperature	-10°C to 50°C	
STANDARD		
Compliance Safety	-15°C to 60°C	
	CE	

Product specifications are subject to change without further notice.